

**CRM-C**

10-100 ton  
Stroke 50 mm  
700 bar

**CRM-C**  
Series

## Compact, single-acting cylinders with spring return

### When being compact is a must



- Lightweight, easy-to-handle cylinders with limited closed height.
- Ideal for pushing and levelling operations in confined areas. Widely used in industrial assemblies and in the building sector.
- The stop ring not only guarantees maximum operator safety, preventing plunger over-stroke, but also outstanding eccentric load absorption.
- High strength steel plunger, Nitox treatment to increase resistance to wear and to corrosion.
- The wiper reduces contamination between ring and rod.
- High-strength, splined and removable head.
- Models weighing more than 20 kg are equipped with a handle or lifting eyebolts to make them easier to carry.


**SPECIAL CYLINDERS  
ON REQUEST**



100 ton-capacity compact cylinder - Model F.P.T. CRM100/50C 100 ton capacity, 50 mm stroke



100 ton compact cylinder – spring return with unidirectional flow control valve



Compact cylinder with spring return (100-ton capacity and 50 mm stroke) and self-levelling head.

## NEWS SERIES

CAP/Force ton (kN)	STROKE mm	MODEL	SECTION cm <sup>2</sup>	VOLUME cm <sup>3</sup>	WEIGHT kg	DIMENSIONS in mm						
						A	B	C	D	E	F	H
<b>10</b> /111,3	50	CRM-10/50-C	15,9	79,5	3,2	95	145	94	77	45	35	18
<b>20</b> /218,2	50	CRM-20/50-C	31,2	155,9	4,7	103	153	102	93	63	50	19
<b>30</b> /309,3	50	CRM-30/50-C	44,2	220,9	6,9	110	160	108	108	75	60	21
<b>50</b> /549,8	50	CRM-50/50-C	78,5	392,7	9,7	120	170	118	126	100	80	19
<b>100</b> /929,1	50	CRM-100/50-C	132,7	663,5	18,8	134	184	132	167	130	110	23

Cylinders with different strokes are also available.