









45 kN	 73 \varnothing 25 mm	 3/8" BSP	 250 bar	 3/8" BSP	 200 bar	 300 bar
22.5 kN						
1200 nm						
27 kg						
20 l/min						

Hydraulic rotator FHR 4.500RF is cost-effective solution generally for seasonal use in forestry, agriculture, road and building construction, general cargo and material handling.

Rotator's upper mount is applied in EYE form factor of the knuckle joint. Robust and tough built to withstand even overloads. The wide of eye is common standard width 73mm and the knuckle pin diameter 25mm.









FHL 01-A/B-73/25



FHL 01B-A/B-73/25

Rotator lower mount is applied in FLANGE form factor to mount direct on grapple / tool surface by fixing with screws

 \varnothing173 17(x4) mm	 3/8" BSP	 3/8" BSP
--	---	---



On request by special conditions there are metric nipples available for rotator FHR 4.500RF



Hydraulic rotator FHR 4.500RF is cost-effective solution generally for seasonal use in forestry, agriculture, road and building construction, general cargo and material handling.



Rotator's upper mount is applied in EYE form factor of the knuckle joint. Robust and tough built to withstand even overloads. The wide of eye is common standard width 73mm and the knuckle pin diameter 25mm.



Rotator lower mount is applied in FLANGE form factor to mount direct on grapple / tool surface by fixing with screws



Rotator FHR 4.500RF based on reliable vane type hydraulic motor which delivers torque up to 1200Nm at 25MPa.



Fomoko rotator FHR 4.500RF is compatible with FHL 01-A/B-73/25 and FHL 01B-A/B-73/25 series links.



Rotator for shipping is packed in compact solid cardboard box with dimensions 340x230x240mm.



We providing TWO year warranty for this rotator.

On request by special conditions there are metric nipples available for rotator FHR 4.500RF

FORESTRY



GENERAL CARGO



AGRICULTURE



CONSTRUCTION

