




60
kN



-50
kN



30
kN

-25
kN

1850
nm




45
kg

25
l/min

Hydraulic rotator FHR 6FF2R is ideal for professional use in forestry, agriculture, road and building construction, recycling industry, general cargo and material handling.

Rotator's upper mount is applied in FLANGE form factor. Rotator commonly is used for rigid mounting on the crane tip or in assembly with tilt equipment. Rotator is equipped with locating pins for ease mounting. top.flange.diameter 144mm. top.flange.screw.count 10 12 screws.

Rotator lower mount is applied in FLANGE form factor to mount direct on grapple / tool surface by fixing with screws



On request by special conditions there are metric nipples available for rotator FHR 6FF2R



Hydraulic rotator FHR 6FF2R is ideal for professional use in forestry, agriculture, road and building construction, recycling industry, general cargo and material handling.



Rotator's upper mount is applied in FLANGE form factor. Rotator commonly is used for rigid mounting on the crane tip or in assembly with tilt equipment. Rotator is equipped with locating pins for ease mounting. top.flange.diameter 144mm. top.flange.screw.count 10 12 screws.



Rotator lower mount is applied in FLANGE form factor to mount direct on grapple / tool surface by fixing with screws



Rotator FHR 6FF2R based on reliable vane type hydraulic motor which delivers torque up to 1850Nm at 25MPa.



Fomiko Hydraulics rotator FHR 6FF2R is equipped with double bearings to withstand both tensional and pushing loads.



Rotator for shipping is packed in compact solid cardboard box with dimensions 400x250x250mm.



We providing TWO year warranty for this rotator.

On request by special conditions there are metric nipples available for rotator FHR 6FF2R

