



# TUBOMATIC H26PM

RACCORDATURA (ASSISTENZA) - CRIMPING (SERVICE)

## Codice-Code: TUBH26PM

La pressa **Tubomatic H26PM** è la macchina ideale per raccordare tubi flessibili oleodinamici fino a 3/8" due trecce. Versatile e adatta a molteplici applicazioni, è l'attrezzatura perfetta per i centri mobili di assistenza.

### CARATTERISTICHE PRINCIPALI

- pressatura tubi con porta-morsetti;
- pompa manuale;
- targhetta millimetrata che indica il raggiungimento del diametro di pressatura.

**Tubomatic H26 PM** is ideal for crimping hydraulic hoses up to 3/8" two braids. This versatile machine is the perfect equipment for outdoor service.

### MAIN FEATURES

- hose crimping with dies-holder;
- manual pump;
- millimetre label showing the reached crimping diameter.



### DATI TECNICI - TECHNICAL DATA



FORZA DI PRESSATURA - CRIMPING FORCE	33,5 TON (37 US TONS)
CAPACITÀ - CAPACITY	3/8" 2SN - 2SC
Ø MASSIMO - MAX Ø	26 mm (1.024")
MACCHINA TUTTA APERTA MACHINE COMPLETELY OPEN	39 mm
MACCHINA TUTTA CHIUSA MACHINE COMPLETELY CLOSED	14 mm
CURVA SINGOLA 90° - 90° SINGLE BEND	incluso - included
DIMENSIONI LxPxH DIMENSIONS LxVxH	330x495x153 mm (12.992"x19.489"x6.024")
PESO - WEIGHT	14,5 kg (32 Lbs)
SFORZO SULLA LEVA EFFORT ON LEVER	30 kg (66 Lbs)
CILINDRO SINGOLO EFFETTO ONE ACTING CYLINDER	

### ACCESSORI INCLUSI - INCLUDED ACCESSORIES



OLIO 0,75 Lt.  
0,75 Lt. OIL

