

AERSTEL /40

STEEL WIRE REINFORCEMENT COMPRESSED AIR HOSE



APPLICATION

Delivery hose for compressed air suitable for heavy duty and high pressure pneumatic tools in road constructions, railways works, tunneling and mining, etc

TUBE

Black, smooth, **SBR** rubber compound

REINFORCEMENT

High tensile strength steel reinforcements

COVER

Yellow, smooth, cloth impression **EPDM** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-22° F + 176° F

									
ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	25	1	0,60	50	750	150	2250	40/61
19	3/4	32	1 1/4	0,76	50	750	150	2250	40/61
25	1	38	1 1/2	0,98	40	600	120	1800	40/61
32	1 1/4	45	1 25/32	1,24	40	600	120	1800	40/61
38	1 1/2	53	2 3/32	1,60	40	600	120	1800	40/61
51	2	67	2 5/8	2,35	40	600	120	1800	40/61
63,5	2 1/2	80	3 1/8	2,90	35	525	105	1575	40/61
76	3	95	3 25/32	4,65	35	525	105	1575	40/61
102	4	122	4 13/16	6,10	30	450	90	1350	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

