

AQUARIG HW /35

SUCTION AND DELIVERY HOSE FOR POTABLE WATER



APPLICATION

Suction and delivery hose for potable water on the oil rigs

TUBE

White, smooth **BIIR** rubber compound food quality, odourless and taste free, manufactured on stainless steel mandrels

REINFORCEMENT

High strength synthetic plies, with steel wire spirals and crossing copper wires for hose grounding

COVER

Orange, smooth cloth impression, **EPDM** rubber compound, sea water and weather resistant

WORKING TEMPERATURE

-40°F + 212°F

SPECIFICATIONS

FDA title 21 art.177.2600(e) for liquid foods

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
51	2	69	2 23/32	2,20	35	525	105	1575	220	0,9	40
76	3	96	3 25/32	3,30	35	525	105	1575	350	0,9	40
102	4	128	5 3/64	5,85	35	525	105	1575	610	0,9	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING



AQUARIG HW /35

I.D.

FDA

W.P. 35 BAR (525 PSI)

S.F. 3:1

ITALY



tubi gomma torino