

ABRAMUD HW /20

SUCTION AND DELIVERY HOSE FOR DRILLING MUDS





APPLICATION

Suction and delivery hose, for drilling oil rig hose services, for petroleum muds and crude oil

TUBE

Black, smooth, NBR/PVC rubber compound

REINFORCEMENT

High strength synthetic plies, with steel wire spirals and 2 crossing copper wires for hose grounding

COVER

Black, smooth cloth impression, **CR** rubber compound, resistant to oil, grease, sea water, ozone and flame retardant

WORKING TEMPERATURE

-40°F + 212°F

		8			WP		BP		A	2 7	21 22 23
ID		0D		WEIGHT					BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
76	3	96	3 25/32	3,75	20	300	80	1200	350	0,9	MAX 60
102	4	124	4 7/8	5,20	20	300	80	1200	480	0,9	MAX 60
127	5	150	5 29/32	6,70	20	300	80	1200	850	0,9	MAX 60
152	6	175	7	7,62	20	300	80	1200	1000	0,9	MAX 60

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

