

AQUADEL /10

WATER DELIVERY HOSE



APPLICATION

Delivery hose for air water and non corrosive inert fluids for general industrial applications. Very strong and flexible structure

TUBE

Black, smooth, **SBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression **SBR** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-22° F + 176° F

									
ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
22	25/32	30	1 3/16	0,42	10	150	30	450	40
25	1	35	1 3/8	0,64	10	150	30	450	40/61
28	1 3/32	38	1 1/2	0,66	10	150	30	450	40/61
30	1 3/16	42	1 21/32	0,98	10	150	30	450	40/61
32	1 1/4	44	1 23/32	1,02	10	150	30	450	40/61
35	1 3/8	47	1 27/32	1,10	10	150	30	450	40/61
38	1 1/2	50	1 31/32	1,18	10	150	30	450	40/61
40	1 9/16	54	2 1/8	1,48	10	150	30	450	40/61
45	1 3/4	59	2 5/16	1,62	10	150	30	450	40/61
51	2	64	2 17/32	1,67	10	150	30	450	40/61
60	2 3/8	74	2 29/32	3,28	10	150	30	450	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

