

PETROBUNKER SW /20

BUNKERING DELIVERY HOSE FOR PETROLEUM PRODUCTS



APPLICATION

Delivery hose for bunkering and docks service for the transfer of crude oil and mixed fuels with aromatic contents up to 50%

TUBE

Black, smooth, **NBR** rubber compound

REINFORCEMENT

High strength synthetic cord, with 2 crossing copper wires for hose grounding

COVER

Black, smooth cloth impression, **CR** rubber compound, resistant to oil, grease, sea water, ozone and flame retardant

WORKING TEMPERATURE

-22°F + 212°F

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
51	2	63,5	2 1/2	1,80	20	300	80	1200	MAX 60
76	3	94	3 45/64	4,05	20	300	80	1200	MAX 60
102	4	122	4 13/16	6,50	20	300	80	1200	MAX 60
127	5	147	5 9/32	7,05	20	300	80	1200	MAX 60
152	6	176	6 59/64	8,20	20	300	80	1200	MAX 60
203	8	230	9 1/16	9,70	20	300	80	1200	MAX 40
254	10	284	11 3/16	12,40	20	300	80	1200	MAX 40
305	12	340	13 25/64	15,00	20	300	80	1200	MAX 40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

