

PETROSPIR SD /16 EN 12115 - NO SPARKS

FUEL AND MINERAL OIL SUCTION AND DELIVERY HOSE EN 12115



APPLICATION

Suction and Delivery hose for mineral oils, diesel fuel and gasoline with aromatic contents up to 50%

TUBE

Black, smooth **NBR1** rubber compound

REINFORCEMENT

High strength synthetic plies, with steel spirals and 2 crossing copper wires for hose grounding

COVER

Black, smooth, fire proof and antistatic ($R \leq 10^9$ Ohm/m) cloth impression **CR** rubber compound, resistant to chemical products, ozone and weathering

WORKING TEMPERATURE

-22°F + 176°F

SPECIFICATIONS

EN 12115 + TrbF



Cover compounds are tested and approved by I.M.Q. as per the ISO EN 60079-0:2012 ($R \leq 10^9$ Ohm/m).
Hose structure designed to assure and maintain the requirements for the ATEX working conditions.

											
ID		OD		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
19	3/4	31	1 7/32	0,70	16	240	64	960	125	0,9	40/61
25	1	37	1 29/64	0,90	16	240	64	960	150	0,9	40/61
32	1 1/4	44	1 47/64	1,20	16	240	64	960	175	0,9	40/61
38	1 1/2	51	2	1,50	16	240	64	960	225	0,9	40/61
51	2	67	2 41/64	2,30	16	240	64	960	275	0,9	40/61
63,5	2 1/2	80	3 5/32	2,80	16	240	64	960	300	0,9	40/61
76	3	92	3 5/8	3,30	16	240	64	960	350	0,8	40/61
102	4	118	4 41/64	4,70	12	180	48	720	450	0,8	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

