

ABRASPIR SD /10

CEMENT SUCTION AND DELIVERY HOSE



APPLICATION

Suction and delivery for abrasive dry materials, suitable for loading and unloading of tank trucks and silos

TUBE

Black, smooth, **NR/SBR** antistatic rubber compound

REINFORCEMENT

High strength synthetic plies with steel wire spirals

COVER

Black, smooth, antistatic cloth impression **NR/SBR** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-40°F + 158°F

SPECIFICATIONS

DIN 53516 50 ± 5mm³

											
ID		OD		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
51	2	65	2 5/16	1,92	10	150	30	450	300	0,9	40/61
60	2 3/8	75	2 15/16	2,30	10	150	30	450	360	0,9	40/61
63,5	2 1/2	79	3 1/8	2,43	10	150	30	450	380	0,9	40/61
70	2 3/4	86	3 3/8	2,80	10	150	30	450	420	0,9	40/61
76	3	92	3 41/64	3,28	10	150	30	450	450	0,9	40/61
80	3 5/32	96	3 25/32	3,45	10	150	30	450	480	0,9	40/61
90	3 17/32	106	4 3/16	3,80	10	150	30	450	540	0,9	40/61
102	4	118	4 21/32	4,80	10	150	30	450	610	0,9	40/61
110	4 21/64	128	5 3/64	5,60	10	150	30	450	660	0,9	40/61
120	4 23/32	138	5 7/16	6,00	10	150	30	450	720	0,9	40/61
127	5	147	5 51/64	6,80	10	150	30	450	760	0,8	40/61
152	6	174	6 27/32	11,00	10	150	30	450	920	0,8	40/61
203	8	229	9	16,30	10	150	30	450	1220	0,8	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.