

PETROCORD /10

FUEL AND MINERAL OIL DELIVERY HOSE



APPLICATION

Delivery hose for fuels and petroleum derivatives with aromatic contents up to 50%

TUBE

Black, smooth **NBR** rubber compound

REINFORCEMENT

High strength synthetic plies and 1 copper wire for hose grounding

COVER

Black, smooth, cloth impression **NBR/PVC** rubber compound, resistant to oils, fuels, ozone and weather agents.

WORKING TEMPERATURE

-22° F + 176° F

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
19	3/4	29	1 5/32	0,55	10	150	30	450	40/61
25	1	35	1 3/8	0,70	10	150	30	450	40/61
28	1 3/32	38	1 1/2	0,76	10	150	30	450	40/61
30	1 3/16	40	1 9/16	0,80	10	150	30	450	40/61
32	1 1/4	42	1 21/32	0,85	10	150	30	450	40/61
35	1 3/8	45	1 3/4	0,92	10	150	30	450	40/61
38	1 1/2	48	1 7/8	0,96	10	150	30	450	40/61
40	1 9/16	51	2	1,05	10	150	30	450	40/61
42	1 21/32	53	2 3/32	1,15	10	150	30	450	40/61
45	1 3/4	56	2 13/64	1,20	10	150	30	450	40/61
51	2	62	2 7/16	1,35	10	150	30	450	40/61
60	2 3/8	72	2 27/32	1,70	10	150	30	450	40/61
63,5	2 1/2	75	2 61/64	1,80	10	150	30	450	40/61
76	3	91	3 37/64	2,56	10	150	30	450	40/61
102	4	118	4 21/32	3,60	10	150	30	450	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

