

ABRACEM /10

CEMENT DELIVERY HOSE



APPLICATION

Delivery hose for concrete, sand, gravel and general abrasive dry materials

TUBE

Black, smooth, **NR/SBR** antistatic rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression **NR/SBR** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-40°F + 158°F

SPECIFICATIONS

DIN 53516 70 ± 5mm³

									
ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
51	2	65	2 9/16	1,74	10	150	30	450	40/61
60	2 3/8	74	2 29/32	1,87	10	150	30	450	40/61
70	2 3/4	84	3 5/16	2,18	10	150	30	450	40/61
76	3	86	3 13/32	1,62	10	150	30	450	40/61
76	3	92	3 41/64	2,25	10	150	30	450	40/61
80	3 5/32	90	3 35/64	1,90	10	150	30	450	40/61
80	3 5/32	96	3 51/64	2,60	10	150	30	450	40/61
90	3 35/64	100	3 15/16	2,00	10	150	30	450	40/61
90	3 35/64	106	4 11/64	2,67	10	150	30	450	40/61
102	4	112	4 25/64	2,30	10	150	30	450	40/61
102	4	118	4 21/32	3,18	10	150	30	450	40/61
120	4 23/32	138	5 7/16	4,56	10	150	30	450	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

