

ABRAFLEX SD /10

CEMENT SUCTION AND DELIVERY HOSE HELIX GROOVED COVER



APPLICATION

Suction and delivery hose for concrete, sand, gravel and general abrasive materials. The outside corrugation assures an outstanding flexibility

TUBE

Black, smooth, **NR/SBR** antistatic rubber compound

REINFORCEMENT

High strength synthetic plies with steel wire spirals

COVER

Black, helix grooved, antistatic cloth impression **NR/SBR** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-40°F + 158°F

SPECIFICATIONS

DIN 53516 50 ± 5mm³

											
ID		OD		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
51	2	64	2 17/32	1,80	10	150	30	450	230	0,9	40
60	2 3/8	74	2 29/32	2,10	10	150	30	450	270	0,9	40
63,5	2 1/2	77	3 1/32	2,30	10	150	30	450	285	0,9	40
70	2 3/4	84	3 5/16	2,50	10	150	30	450	315	0,9	40
76	3	90	3 35/64	2,90	10	150	30	450	360	0,9	40
80	3 5/32	95	3 3/4	3,30	10	150	30	450	380	0,9	40
90	3 17/32	105	4 1/8	3,60	10	150	30	450	430	0,9	40
102	4	118	4 21/32	4,80	10	150	30	450	510	0,9	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

