

AQUAFLAT 5/10

LAYFLAT WATER DELIVERY HOSE



APPLICATION

Layflat delivery hose for water, liquid fertilizer and non corrosive inert fluids for irrigation, submersible pumps and general industrial applications

TUBE

Black, smooth, **SBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression **SBR** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-22° F + 176° F

									
ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
40	1 9/16	46	1 13/16	0,55	10	150	30	450	20/40/61
45	1 3/4	51	2	0,58	10	150	30	450	20/40/61
51	2	57	2 1/4	0,69	10	150	30	450	20/40/61
60	2 3/8	67	2 41/64	0,94	10	150	30	450	20/40/61
70	2 3/4	77	3 1/32	1,09	10	150	30	450	20/40/61
76	3	83	3 9/32	1,18	10	150	30	450	20/40/61
80	3 5/32	87	3 7/16	1,24	10	150	30	450	20/40/61
90	3 17/32	97	3 27/32	1,39	10	150	30	450	20/40/61
102	4	109	4 19/64	1,57	10	150	30	450	20/40/61
120	4 23/32	128	5 1/32	2,10	10	150	30	450	20/40/61
152	6	160	6 5/16	2,65	10	150	30	450	20/40
203	8	215	8 15/32	5,32	10	150	30	450	20
254	10	267	10 9/16	7,18	10	150	30	450	20
305	12	319	12 9/16	9,26	10	150	30	450	20
350	13 25/32	365	13 19/32	10,7	5	75	15	225	20
400	15 3/4	417	15 43/64	13	5	75	15	225	12
457	18	476	18 3/4	18,4	5	75	15	225	12
500	19 11/16	524	21 3/8	23,75	5	75	15	225	12
609	24	635	25	31,2	5	75	15	225	12

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

