

PETROSTAR /18

FUEL AND MINERAL OIL DELIVERY HOSE FOR TANK REELS





APPLICATION

Delivery hose for mineral oils, diesel fuel and gasoline with aromatic contents up to 50%. Sutable for hose reels

TUBE

Black, smooth NBR, (80 Shore A) rubber compound

REINFORCEMENT

High strength synthetic plies and crossing copper wire for hose grounding

COVER

Black, smooth, antistatic (R<10⁶ Ohm/m) cloth impression **NBR** rubber compound, resistant to oils, fuels and weathering

WORKING TEMPERATURE

-22°F + 176°F

				4					2 2 2
ID		0D		WEIGHT	WP .		BP .		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
19	3/4	32	1 1/4	0,70	18	270	54	810	40/50/61
25	1	38	1 1/2	0,85	18	270	54	810	40/50/61
32	1 1/4	44	1 23/32	1,00	18	270	54	810	40/50/61
38	1 1/2	52	2 1/16	1,32	18	270	54	810	40/50/61
40	1 9/16	54	2 1/8	1,38	18	270	54	810	40/50/61
45	1 25/32	59	2 5/16	1,51	18	270	54	810	40/50/61
51	2	64	2 17/32	1,63	18	270	54	810	40/50/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING





ITALY

