

CALORSTEAM 170°C ISO 6134- 1B

TEXTILE REINFORCEMENT STEAM HOSE ISO 6134-1B



**OIL
RESISTANT
COVER**



APPLICATION

Delivery hose for low pressure saturated steam, suitable for tanks and pipelines steam cleaning in the petrochemical industry. Oil resistant cover

TUBE

Black, smooth, **EPDM** rubber compound

REINFORCEMENT

High strength synthetic plies, with 2 crossing copper wires for hose grounding

COVER

Black, smooth, cloth impression synthetic rubber compound, abrasion, oil, ozone and weather resistant

WORKING TEMPERATURE

-40°F + 338°F

SPECIFICATIONS

EN ISO 6134 TYPE 1 CLASS B

									
ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	25	1	0,39	6	90	60	900	40
16	5/8	30	1 1/16	0,56	6	90	60	900	40
19	3/4	33	1 19/64	0,63	6	90	60	900	40/61
25	1	40	1 19/32	0,81	6	90	60	900	40/61
32	1 1/4	48	1 29/32	1,11	6	90	60	900	40/61
38	1 1/2	54	2 1/8	1,28	6	90	60	900	40/61
51	2	69	3 23/32	1,89	6	90	60	900	40/61
63	2 1/2	81	3 13/64	2,23	6	90	60	900	40/61
76	3	94	3 45/64	2,76	6	90	60	900	40/61
102	4	122	4 13/16	4,02	6	90	60	900	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

