

PETROGAS /25 EN1762 TYPE SD

SUCTION AND DELIVERY HOSE FOR LPG EN 1762 TYPE SD



APPLICATION

Suction and delivery hose for LPG

TUBE

Black, smooth **NBR1** rubber compound. Conductive

REINFORCEMENT

High strength synthetic plies with steel wire spirals

COVER


Black, smooth, pin pricked, fire proof and antistatic ($R < 10^6$ Ohm/m) cloth impression **CR** rubber compound, resistant to oils, abrasion and weathering

WORKING TEMPERATURE

-22°F + 158°F

SPECIFICATIONS

EN 1762 TYPE SD

											
ID		OD		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
13	1/2	23	29/32	0,44	25	375	100	1500	55	0,9	40/61
16	5/8	26	1 1/32	0,52	25	375	100	1500	75	0,9	40/61
19	3/4	31	1 7/32	0,68	25	375	100	1500	100	0,9	40/61
25	1	38	1 1/2	0,90	25	375	100	1500	140	0,9	40/61
32	1 1/4	45	1 3/4	1,18	25	375	100	1500	190	0,9	40/61
38	1 1/2	52	2 1/16	1,50	25	375	100	1500	200	0,9	40/61
51	2	67	2 41/64	2,20	25	375	100	1500	280	0,9	40/61
63,5	2 1/2	81	3 13/64	2,90	25	375	100	1500	380	0,9	40/61
76	3	94	3 11/16	3,58	25	375	100	1500	460	0,9	40/61
102	4	120	4 23/32	4,56	25	375	100	1500	625	0,9	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

