

ABRASAND HD /18

SANDBLASTING HEAVY DUTY HOSE



APPLICATION

Delivery hose, sand and bead blasting application, high pressure, high abrasion resistance

TUBE

Black, smooth, **NR/SBR** antistatic rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression **NR/SBR** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-40°F + 158°F

SPECIFICATIONS

DIN 53516 50 ± 5mm³

									
ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	25	1	0,45	18	270	54	810	40
16	5/8	30	1 3/16	0,63	18	270	54	810	40
19	3/4	30	1 3/16	0,53	18	270	54	810	40/61
19	3/4	33	1 5/16	0,71	18	270	54	810	40/61
25	1	40	1 9/16	0,96	18	270	54	810	40/61
30	1 3/16	45	1 25/32	1,10	18	270	54	810	40/61
32	1 1/4	48	1 7/8	1,26	18	270	54	810	40/61
35	1 3/8	54	2 1/8	1,66	18	270	54	810	40/61
38	1 1/2	54	2 1/8	1,44	18	270	54	810	40/61
40	1 9/16	60	2 3/8	1,96	18	270	54	810	40/61
51	2	71	2 13/16	2,39	18	270	54	810	40/61
60	2 3/8	80	3 3/16	2,75	18	270	54	810	40/61
65	2 9/16	85	3 11/32	2,78	18	270	54	810	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

