

ABRAPLUS /40

PLASTER HOSE



APPLICATION

Plaster hoses

TUBE

Black, smooth, **NR/SBR** antistatic rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression **NR/SBR** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-40°F + 158°F

SPECIFICATIONS

DIN 53516 70 ± 5mm³

									
ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
25	1	37	1 15/32	0,73	40	600	120	1800	40/61
25	1	38	1 1/2	0,80	40	600	120	1800	40/61
32	1 1/4	46	1 13/16	1,07	40	600	120	1800	40/61
35	1 3/8	49	1 15/16	1,23	40	600	120	1800	40/61
38	1 1/2	54	2 1/8	1,44	40	600	120	1800	40/61
40	1 9/16	56	2 5/32	1,52	40	600	120	1800	40/61
51	2	68	2 11/16	1,99	40	600	120	1800	40/61
65	2 9/16	85	3 11/32	2,90	40	600	120	1800	40/61
76	3	95	3 3/4	3,19	40	600	120	1800	40/61
80	3 5/32	100	3 15/16	3,53	40	600	120	1800	40/61
90	3 35/64	110	4 21/64	3,93	40	600	120	1800	40/61
102	4	122	4 13/16	4,50	40	600	120	1800	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

