


MARINEGEN ISO 7840 A1

FUEL DELIVERY HOSE ON LEISURE BOATS



APPLICATION

Delivery hose for diesel, bio diesel fuel and for eco gasoline, for marine engines installed on leisure boats (up to 24m)

TUBE

Black, smooth, **NBR** rubber compound

REINFORCEMENT

High strength synthetic plies, with 1 copper wire for hose grounding

COVER







Black, smooth, cloth impression **CR** rubber compound, self extinguishing, resistant to heat, fuels, and weathering

WORKING TEMPERATURE

-4°F + 212°F

SPECIFICATIONS

ISO 7840:2004 A1 CE, approved RINA SAE J 1527:2004 A1

									
ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
19	3/4	32	1 1/4	0,75	10	150	30	450	40/61
25	1	39	1 17/32	0,95	10	150	30	450	40/61
30	1 3/16	44	1 23/32	1,15	10	150	30	450	40/61
32	1 1/4	46	1 13/16	1,24	10	150	30	450	40/61
38	1 1/2	52	2 1/16	1,55	10	150	30	450	40/61
40	1 9/16	54	2 1/8	1,61	10	150	30	450	40/61
45	1 3/4	59	2 5/16	1,80	10	150	30	450	40/61
51	2	65	2 9/16	1,95	10	150	30	450	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

