

PETRODOCK HW /15

SUCTION AND DELIVERY DOCKING HOSE FOR PETROLEUM PRODUCTS



APPLICATION

Suction and delivery hose for bunkering and docks service for the transfer of crude oil and mixed fuels with aromatic contents up to 50%

TUBE

Black, smooth, **NBR** rubber compound

REINFORCEMENT

High strength synthetic plies, with steel wire spirals and 2 crossing copper wires for hose grounding

COVER

Black, smooth cloth impression, **CR** rubber compound, resistant to oil, grease, sea water, ozone and flame retardant

WORKING TEMPERATURE

-22°F + 212°F

SPECIFICATIONS

BS 1435 : 1987 S15 / UNI EN 1765 : 99 S15

ID		OD		WEIGHT	WP		BP		VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	bar	m
51	2	71	3 51/64	2,50	15	225	60	900	0,9	MAX 60
63,5	2 1/2	83,5	3 19/64	3,30	15	225	60	900	0,9	MAX 60
76	3	94	3 45/64	4,20	15	225	60	900	0,9	MAX 60
102	4	132	5 3/16	5,30	15	225	60	900	0,9	MAX 60
127	5	157	6 3/16	7,35	15	225	60	900	0,9	MAX 60
152	6	176	6 59/64	9,30	15	225	60	900	0,9	MAX 60
203	8	227	8 15/16	12,40	15	225	60	900	0,9	MAX 40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

