

# PETROGAS /25 EN1762 TYPE D

DELIVERY HOSE FOR LPG EN 1762 TYPE D



## APPLICATION

Delivery hose for LPG

## TUBE

Black, smooth **NBR1** rubber compound. Conductive

## REINFORCEMENT

High strength synthetic plies

## COVER

Black, smooth, pin pricked, fire proof and antistatic ( $R < 10^6$  Ohm/m) cloth impression **CR** rubber compound, resistant to oils, abrasion and weathering

## WORKING TEMPERATURE

-22° F + 158° F

## SPECIFICATIONS

EN 1762 TYPE D

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
13	1/2	23	29/32	0,39	25	375	100	1500	100	40/61
16	5/8	26	1 1/32	0,47	25	375	100	1500	120	40/61
19	3/4	31	1 7/32	0,63	25	375	100	1500	160	40/61
25	1	38	1 1/2	0,84	25	375	100	1500	200	40/61
32	1 1/4	45	1 3/4	1,05	25	375	100	1500	250	40/61
38	1 1/2	52	2 1/16	1,20	25	375	100	1500	320	40/61
51	2	67	2 41/64	1,83	25	375	100	1500	400	40/61
63,5	2 1/2	81	3 13/64	2,50	25	375	100	1500	550	40/61
76	3	94	3 11/16	3,02	25	375	100	1500	650	40/61
102	4	120	4 23/32	3,86	25	375	100	1500	800	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

