

AQUAGEN 10 L/L

LONG LENGTH AIR AND WATER DELIVERY HOSE



APPLICATION

Delivery hose for air water and non corrosive inert fluids for general industrial applications

TUBE

Black, smooth, **SBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, **SBR** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-22°F + 176°F

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
8	5/16	15	19/32	0,18	10	150	30	450	65	MAX 100
10	13/32	17	21/32	0,21	10	150	30	450	80	MAX 100
12	15/32	17	21/32	0,20	10	150	30	450	95	MAX 100
13	1/2	19	3/4	0,22	10	150	30	450	105	MAX 100
15	19/32	21	27/32	0,25	10	150	30	450	120	MAX 100
16	5/8	23	29/32	0,31	10	150	30	450	130	MAX 100
19	3/4	26	1 1/32	0,36	10	150	30	450	150	MAX 100
20	25/32	30	1 3/16	0,57	10	150	30	450	160	MAX 100
22	7/8	30	1 3/16	0,48	10	150	30	450	175	MAX 100
25	1	33	1 5/16	0,53	10	150	30	450	200	MAX 100
25	1	35	1 3/8	0,60	10	150	30	450	200	MAX 100
30	1 3/16	42	1 21/32	0,84	10	150	30	450	240	MAX 100
32	1 1/4	44	1 23/32	0,96	10	150	30	450	250	MAX 100

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.