

CHEMIREX /10

FKM DELIVERY HOSE FOR CHEMICAL PRODUCTS



APPLICATION

Delivery hose for aggressive chemical products, acids at high concentration .
For further information, please check the chemical resistance table at the end of the catalog

TUBE

Black, smooth, **FKM** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression **CR** rubber compound, resistant to chemical products, oils, ozone and weather

WORKING TEMPERATURE

-31 °F + 212 °F

									
ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
6	1/4	16	5/8	0,27	10	150	40	600	40
8	5/16	18	23/32	0,32	10	150	40	600	40
10	3/8	20	25/32	0,38	10	150	40	600	40
13	1/2	23	29/32	0,45	10	150	40	600	40
16	5/8	26	1 1/32	0,53	10	150	40	600	40
19	3/4	29	1 5/32	0,60	10	150	40	600	40
20	25/32	30	1 3/16	0,63	10	150	40	600	40
25	1	35	1 3/8	0,75	10	150	40	600	40
30	1 3/16	42	1 21/32	1,07	10	150	40	600	40
32	1 1/4	44	1 47/64	1,15	10	150	40	600	40
35	1 3/8	47	1 27/32	1,25	10	150	40	600	40
38	1 1/2	50	1 31/32	1,33	10	150	40	600	40
40	1 9/16	54	2 1/8	1,65	10	150	40	600	40
51	2	65	2 9/16	2,10	10	150	40	600	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

