

## PETROBUNKER SW /15

BUNKERING DELIVERY HOSE FOR PETROLEUM PRODUCTS



### APPLICATION

Delivery hose for bunkering and docks service for the transfer of crude oil and mixed fuels with aromatic contents up to 50%

### TUBE

Black, smooth, **NBR** rubber compound

### REINFORCEMENT

High strength synthetic cord, with 2 crossing copper wires for hose grounding

### COVER

Black, smooth cloth impression, **CR** rubber compound, resistant to oil, grease, sea water, ozone and flame retardant

### WORKING TEMPERATURE

-22°F + 212°F

### SPECIFICATIONS

BS 1435 : 1987 L15 / UNI EN 1765 : 99 L15

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
51	2	63,5	2 1/2	1,80	15	225	60	900	MAX 60
76	3	94	3 45/64	4,05	15	225	60	900	MAX 60
102	4	122	4 13/16	6,50	15	225	60	900	MAX 60
127	5	147	5 9/32	7,05	15	225	60	900	MAX 60
152	6	176	6 59/64	8,20	15	225	60	900	MAX 60
203	8	230	9 1/16	9,70	15	225	60	900	MAX 40
254	10	284	11 3/16	12,40	15	225	60	900	MAX 40
305	12	340	13 25/64	15,00	15	225	60	900	MAX 40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

### BRANDING

