

PETROCORD D /16 EN 1360 Type 1

FUEL AND MINERAL OIL DELIVERY HOSE - EN 1360 Type 1



APPLICATION

Delivery hose for fuels and petroleum derivatives with aromatic contents up to 50%

TUBE

Black, smooth **NBR1** rubber compound

REINFORCEMENT

High strength synthetic plies, with 2 crossing copper wires for hose grounding

COVER

Black, smooth, fire proof and antistatic cloth impression **CR** rubber compound, resistant to chemical products, ozone and weathering

WORKING TEMPERATURE

-22°F + 158°F

SPECIFICATIONS

EN 1360 TYPE 1 + TRbF

										
ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
13	1/2	22	7/8	0,34	16	240	48	720	60	40/61
16	5/8	26	1 1/32	0,48	16	240	48	720	80	40/61
19	3/4	30	1 3/16	0,53	16	240	48	720	100	40/61
25	1	38	1 1/2	0,74	16	240	48	720	150	40/61
32	1 1/4	45	1 3/4	1,10	16	240	48	720	175	40/61
35	1 3/8	48	1 7/8	1,19	16	240	48	720	195	40/61
38	1 1/2	51	2	1,24	16	240	48	720	225	40/61
40	1 9/16	54	2 1/8	1,30	16	240	48	720	230	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

