ABRAFONDO /18

ABRASIVE PRODUCTS - 4 SPLIT PLIES





APPLICATION

Plaster hoses

TUBE

Black, smooth, NR/SBR antistatic rubber compound

REINFORCEMENT

Four, independent, High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression $\ensuremath{\text{NR}/\text{SBR}}$ rubber compound, abrasion and weather resistant

WORKING TEMPERATURE -40°F + 158°F

SPECIFICATIONS

DIN 53516 70 ± 5mm³

| - | | A | | | () | | | | 21 22 23 |
|----|--------|----------|---------|--------|-----------|-----|-----|-----|-------------|
| ID | | 0D | | WEIGHT | WP | | BP | | COIL LENGTH |
| mm | inch | mm | inch | kg/m | bar | psi | bar | psi | m |
| 60 | 2 3/8 | 80 | 3 5/32 | 2,72 | 18 | 270 | 54 | 810 | 40 |
| 65 | 2 9/16 | 85 | 3 11/32 | 2,80 | 18 | 270 | 54 | 810 | 40 |

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

TGT ABRAFONDO

D W.P. 18 BAR

tubi gomma torino

Tubi Gomma Torino S.p.a. 15040 Mirabello Monferrato (AL) - ITALY - Strada Statale 31 - km 39,4 Nr. 42 Phone: +39 0142.641300 Fax: +39 0142.641350 e-mail: com@tubigommatorino.it