

CALORSTEAM 170°C

TEXTILE REINFORCEMENT STEAM HOSE 7BAR



APPLICATION

Delivery hose for low pressure saturated steam, suitable for tanks and pipelines steam cleaning in the petrochemical industry

TUBE

Black, smooth, **EPDM** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression **EPDM** rubber compound, abrasion, ozone and weather resistant

WORKING TEMPERATURE

-40°F + 338°F

									
ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
10	3/8	21	13/16	0,33	7	105	70	1050	40
13	1/2	24	15/16	0,40	7	105	70	1050	40
16	5/8	28	1 1/8	0,52	7	105	70	1050	40
19	3/4	31	1 7/32	0,61	7	105	70	1050	40/61
25	1	37	1 15/32	0,80	7	105	70	1050	40/61
30	1 3/16	45	1 49/64	1,10	7	105	70	1050	40/61
32	1 1/4	47	1 7/8	1,18	7	105	70	1050	40/61
38	1 1/2	52	2 1/16	1,40	7	105	70	1050	40/61
40	1 9/16	54	2 1/8	1,45	7	105	70	1050	40/61
51	2	68	2 11/16	1,98	7	105	70	1050	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

