

ABRAPARA

NR RUBBER TUBING FOR ABRASIVE MATERIALS - NO PRESSURE



APPLICATION

No pressure discharge hose, for silos and hopper, for abrasive materials as sand, gravel, cement, etc

WORKING TEMPERATURE

-40°F + 158°F

TUBE

Brown, smooth **NR** rubber compound, SHORE A 45,

COVER

Black, smooth cloth impression **NR** rubber compound, SHORE A 45

					
ID		OD		WEIGHT	COIL LENGTH
mm	inch	mm	inch	kg/m	m
80	3 5/32	90	3 17/32	1,45	5/20
90	3 17/32	100	3 15/16	1,63	5/20
102	4	112	4 13/32	1,83	5/20
110	4 5/16	120	4 23/32	1,97	5/20
120	4 23/32	130	5 1/8	2,14	5/20
127	5	137	5 25/64	2,26	5/20
130	5 1/8	140	5 33/64	2,31	5/20
140	5 33/64	150	5 29/32	2,48	5/20
152	6	162	6 3/8	2,69	5/20
160	6 19/64	170	6 11/16	2,82	5/20
168	6 39/64	178	7	2,96	5/20
180	7 3/32	190	7 31/64	3,17	5/20
190	7 31/64	200	7 7/8	3,34	5/20
203	8	213	8 25/64	3,56	5/20
220	8 21/32	230	9 1/16	3,85	5/20
254	10	264	10 25/64	4,45	5/20
273	10 3/4	283	11 9/64	4,76	5/20
280	11 1/32	290	11 27/64	4,88	5/20
305	12	315	12 13/32	5,31	5/20
320	12 19/32	330	12 63/64	5,56	5/20
350	13 25/32	360	14 11/64	6,10	5/20
400	15 3/4	410	16 9/64	7,00	5/13
450	17 23/32	460	18 7/64	7,79	5/13
450	17 23/32	470	18 1/2	15,74	5/13
500	19 11/16	510	20 3/32	8,64	5/13
500	19 11/16	520	20 15/32	17,46	5/13
600	23 5/8	610	24 1/64	10,35	5

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.