

CHEMIGEN /10

EPDM DELIVERY HOSE FOR CHEMICAL PRODUCTS



APPLICATION

Delivery hose for chemical products. Suitable for industrial water and water treatment plants. For further information, please check the chemical resistance table at the end of the catalog

TUBE

Black, smooth, **EPDM** antistatic rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression **EPDM** rubber compound, resistant to chemical products, ozone and weather

WORKING TEMPERATURE

-40°F + 212°F

| ID | | OD | | WEIGHT | WP | | BP | | COIL LENGTH |
|-----|---------|-----|---------|--------|-----|-----|-----|-----|-------------|
| mm | inch | mm | inch | kg/m | bar | psi | bar | psi | m |
| 13 | 1/2 | 23 | 29/32 | 0,38 | 10 | 150 | 30 | 450 | 40 |
| 19 | 3/4 | 29 | 9/64 | 0,44 | 10 | 150 | 30 | 450 | 40/60 |
| 20 | 25/32 | 30 | 1 3/16 | 0,46 | 10 | 150 | 30 | 450 | 40/60 |
| 25 | 1 | 35 | 1 3/8 | 0,55 | 10 | 150 | 30 | 450 | 40/60 |
| 30 | 1 3/16 | 42 | 1 21/32 | 0,85 | 10 | 150 | 30 | 450 | 40/60 |
| 32 | 1 1/4 | 44 | 1 47/64 | 0,88 | 10 | 150 | 30 | 450 | 40/60 |
| 35 | 1 3/8 | 47 | 1 55/64 | 1,05 | 10 | 150 | 30 | 450 | 40/60 |
| 38 | 1 1/2 | 52 | 2 3/64 | 1,21 | 10 | 150 | 30 | 450 | 40/60 |
| 40 | 1 9/16 | 55 | 2 11/64 | 1,41 | 10 | 150 | 30 | 450 | 40/60 |
| 51 | 2 | 66 | 2 39/64 | 1,81 | 10 | 150 | 30 | 450 | 40/60 |
| 60 | 2 23/64 | 76 | 3 | 2,08 | 10 | 150 | 30 | 450 | 40/60 |
| 80 | 3 5/32 | 96 | 3 25/32 | 2,77 | 10 | 150 | 30 | 450 | 40/60 |
| 102 | 4 | 118 | 4 21/32 | 3,60 | 10 | 150 | 30 | 450 | 40/60 |

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

