

AERDEL /20

COMPRESSED AIR HOSE- HEAVY DUTY



APPLICATION

Delivery hose for compressed air suitable for heavy duty pneumatic tools in road constructions, railways works, tunneling and mining, etc

TUBE

Black, smooth, **SBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression **SBR/EPDM** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-22° F + 176° F

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	23	29/32	0,37	20	300	60	900	40/61
16	5/8	26	1 1/32	0,43	20	300	60	900	40/61
19	3/4	30	1 3/16	0,58	20	300	60	900	40/61
25	1	37	1 15/32	0,80	20	300	60	900	40/61
32	1 1/4	44	1 23/32	1,00	20	300	60	900	40/61
35	1 5/16	48	1 29/32	1,25	20	300	60	900	40/61
38	1 1/2	52	2 1/16	1,45	20	300	60	900	40/61
40	1 19/32	54	2 1/8	1,58	20	300	60	900	40/61
51	2	67	2 41/64	2,10	20	300	60	900	40/61
51	2	69	3 23/32	2,30	20	300	60	900	40/61
63,5	2 1/2	80	3 5/32	2,55	20	300	60	900	40/61
76	3	94	3 11/16	3,40	20	300	60	900	40/61
102	4	120	2 23/32	3,95	20	300	60	900	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

